

CV-NPS-2G004-GE-RO

- 4*10/100/1000Mbps PoE ports
- 1*1000Mbps Uplink port
- 1*1000Mbps SFP Slot
- Support IEEE802.3af/at
- Support restrain network storm, VLAN function
- Transmission distance upto 100/250m
- All Port Supported by MDI/MDIX auto flip
- Built in power supply
- Maximum power of single PoE port: 30 W
- Whole machine power: 120W
- Adopts store and forward architecture
- Fanless, natural cooling, small, compact and quiet design
- Support lightning protection 4KV



PLUG & PLAY
Installation



250M LONG RANGE POE
Upto 250 Transmission



MULTICAST
Optimization



5KV SURGE PROOF
Upto 5K Lighting Protection

Technical Specification

MODEL	CV-NPS-2G004-GE-RO
Power Adapter Voltage	AC 110V-240V
Consumption	120W(52V 2.3A)
PoE Ethernet Port	1-4 port:10/100Mbps
Ethernet Port	Uplink port: 1000Mbps, SFP port: 1000Mbps
Transmission Distance	1000Mbps:0-100m / 1000Mbps, Uplink Port:0-80m / 1000Mbps, SFP Port: As Per Module, 10Mbps:0-250m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.3ab
Switching Capacity	12Gbps
Packet Buffer Memory	1Mbits
Throughput	8.928Mbps
MAC Table	2K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:148800pps/port, 1000Mbps:1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	1/2 +,3/6 -
PoE Power	af=15.4w,at=30w for each port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 1000Mbps: PoE Status Indicator, Power Indicator, Extender
Working temperature	0 C°~55 C°
Relative Humidity	20-95%
Storage temperature	-20 C°~70 C°
Dimension(L*W*H)	220mm*140mm*45mm
Color & Weight	Black 1.05Kg

Note: *Product casing and specifications are subject to change without prior notice..

✉ mail@ciview.in

🌐 www.ciview.in

📱 Follow us

