

CV-NPS-2G008-GE-2SF-RO

- 8*1000Mbps PoE ports
- 2*1000Mbps Uplink port
- 2*1000Mbps SFP Port
- Support IEEE802.3af/at
- Support restrain network storm,
- All port supported by MDI/MDIX auto flip & self-negotiation
- Built-in power supply
- Maximum power of single PoE port: 30W
- Maximum PoE power: 150W
- Adopts store-and-forward architecture
- Fanless, natural cooling, small compact and quiet design, suitable for desktop or wall
- Support lightning protection 4KV



PLUG & PLAY
Installation



LONG RANGE POE
Upto 250 Transmission



MULTICAST
Optimization



SURGE PROOF
Upto 5K Lightning Protection

Technical Specification

MODEL	CV-NPS-2G008-GE-2SF-RO
Power Adapter Voltage	AC 110V-240V
Consumption	150W(52V 2.88A)
PoE Ethernet Port	1-8 port:1000Mbps
Ethernet Port	Uplink port:1000Mbps, 2*SFP Port
Transmission Distance	1-8 Port :1000M: 0-100m / Uplink Port:0-100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u, IEEE802.3x, IEEE802.1ab
Switching Capacity	20Gbps
Packet Buffer Memory	1Mbits
Throughput	14.88Mbps
MAC Table	2K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:148800pps/port, 1000Mbps:1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	1/2(+), 4/5(-), 3/6(-), 7/8(-)
PoE Power	af=15.4w, at=30w for each port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	Power indicator: keep bright when connect power Network indicator: Flicker when there is data transmission
Working temperature	0°C~55°C
Relative Humidity	20-95%
Storage temperature	-20°C~70°C
Dimension(L*W*H)	220mm*140mm*45mm
Color & Weight	Black 1.05Kg

Note: *Product casing and specifications are subject to change without prior notice..

✉ mail@ciview.in

🌐 www.ciview.in

📱 Follow us

