NETWORK
POE SWITCH

CI VIEW®
Keeping You Safe

CV-NPS-2008-FE-RO

- 8*10/100Mbps PoE ports
- 2*10/100Mbps uplink port
- Support IEEE802.3af/at
- Support restrain network storm
- Max Transmission distance up to 250m
- Built-in power supply
- Maximum power of single PoE port: 30W
- Maximum PoE power: 120W
- Adopts store-and-forward architecture
- Fanless, natural cooling, small
- Compact and quiet design
- suitable for desktop or wall
- Support lightning protection 2KV

PLUG & PLAY
Installation

250M **LONG RANGE POE**
Upto 250 Transmission

MULTICAST
Optimization

5KV **SURGE PROOF**
Upto 5K Lighting Protection

Technical Specification

MODEL	CV-NPS-2008-FE-RO
Power Adapter Voltage	AC 110V-240V
Consumption	120W(52V 2.3A)
PoE Ethernet Port	1-8 port:10/100Mbps
Ethernet Port	Uplink port:10/100Mbps
Transmission Distance	100Mbps:0-100m / 10Mbps:0-250m / Uplink Port:0-100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.3ab
Switching Capacity	2Gbps
Packet Buffer Memory	1Mbits
Throughput	1.488Mbps
MAC Table	1K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	1/2 +,3/6 -,8 core power supply
PoE Power	af=15.4w,at=30w for each port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 100Mbps: PoE Status Indicator, Power Indicator, Extender
Working temperature	0˚C~55˚C
Relative Humidity	20-95%
Storage temperature	-20˚C~70˚C
Dimension(L*W*H)	220mm*140mm*45mm
Color & Weight	Black 1.05Kg

Note: *Product casing and specifications are subject to change without prior notice..

mail@ciview.in
www.ciview.in
Follow us